



**DECLARATION OF PERFORMANCE**  
**No. 0780 – CPD – BBW 0216010/2**

1. Unique identification code of the product-type:  
**Portland cement EN 197-1 CEM I 52,5 N white**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):  
**Portland cement EN 197-1 CEM I 52,5 N white**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Preparation of concrete, mortar, grout etc.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):  
**Holcim (Slovensko) a.s. 906 38 Rohožník, plant Rohožník, Slovenská republika**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):  
**Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:  
**System 1+**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**Notified product certification body No. 0780 TÜV Rheinland LGA Bautechnik GmbH, Baustoffe und Betontechnologie, Tillystraße 2, 904 31 Nürnberg, Germany performed the determination of the product-type on the basis of type testing (including sampling), the initial inspection of the manufacturing plant and of factory production control, the continuous surveillance, assessment and evaluation of factory production control and the audit-testing of samples taken before placing the product on the market under system 1+ and issued the certificate of constancy of performance EC Certificate of compliance No. 0780 – CPD – BBW 0216010/2**

8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Compression strength 2 days	≥ 20,0 MPa	EN 197-1:2011
Compression strength 28 days	≥ 52,5 MPa	
Initial setting time	≥ 45 min.	
Volume constancy	≤ 10 mm	
Sulphate content	≤ 4,0 % mass	
Insoluble residue	≤ 5,0 % mass	
Chloride content	≤ 0,1 % mass	
Ignition loss	≤ 5,0 % mass	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Pedro Miñarro Jodar  
Director of plant Rohožník  
At Rohožník, 01.07.2013

  
Signature