

Technical Data Sheet

SINIAT gypsum plaster, Grade G4/A2 (from Romania)

Ready-mixed, high quality natural gypsum plaster for use in buildings and other construction projects.

Where to use	Can be used as a hydraulic binder for buildings and other construction projects, for securing electric cables, sleeve pipes and junction boxes in place quickly and easily, for fixing plumbing and sanitary pipes, for filling holes and gaps, for repairing and filling plaster defects, and for plastering in general. For special uses consult the manufacturer or the distributor.	
Application	Slowly add the plaster to tap water and mix it constantly to obtain a homogenous and lump-free mix of the right density. The mixed gypsum plaster should be used within approximately 10-12 minutes, before it starts to set. Do not use the material if the hardening process has already started! After use your tools should be rinsed with plenty of water. Not recommended for use in temperatures below +5°C.	
Technical data	Date of manufacture:	see label on the bag
	MSZ EN:	13279
	Declaration of performance number:	STK 1-2013
	Tariff heading:	25202000
Packaging	Available in 25 kg paper bags, 48 bags/pallet in 5 kg plastic bags, 200 bags/pallet, in heat-shrink wrapping in 2 kg plastic bags, 500 bags/pallet, in heat-shrink wrapping	
Storage	In a covered place, in dry conditions, for approximately 6 months from the date of manufacture, in unopened bags	
Manufacturer	Siniat SA, Aghires, Romania	
Distributor	Széria-Trans Kereskedelmi és Szolgáltató Kft. H-1116 Budapest, Adony u. 7, Phone: +36-1-466-7758 H-5300 Karcag, Tilalmasi út 1, Phone: +36-59-311-333	